Firestone Building Products Company, LLC Material Safety Data Sheet

April 29, 2011 Page: 1

Product Name: Peel & Stick Rubber Roofing (Black) Products

Chemical Name / Synonym: Peel & Stick Flashing (Black), Peel & Stick Cover Tape

> (Black), Peel & Stick Pipe Boot (Black), Peel & Stick Corner (Black), Peel & Stick RPS (Black), Peel & Stick Seam Tape

(Black)

Chemical Family: Mixture

(800) 424-9300 CHEMTREC 24-Hour Emergency Phone:

Manufacturer's Name: Firestone Building Products Company, LLC 250 West 96th Street, Indianapolis, IN 46260 Manufacturer's Address:

Health 1, Flammability 1, Reactivity 0 NFPA Hazard Rating: HMIS Hazard Rating: Health 0, Flammability 1, Reactivity 0

SECTION 2: CHEMICAL COMPOSITION

Common

CAS #: **Chemical Name:** Name: % (by wt) **Exposure Limits:**

Nonhazardous as per 29 CFR 1910.1200.

None None 100.00 Nonhazardous as per 29 CFR 1910.1200

SECTION 3: HAZARD IDENTIFICATION

Primary Route of Exposure: Eve contact

Signs and Symptoms of Contact with eye may result in irritation, redness, tearing and

Exposure: blurred vision. None known.

Medical Conditions Aggravated

by Exposure: Chronic Effects:

No known adverse effects.

Carcinogenicity: None

SECTION 4: FIRST AID MEASURES

First Aid Procedures: Treat as a foreign object in eye. Flush large amounts of

water, frequently flushing under the lids. Get medical

attention if irritation persists.

SECTION 5: FIRE FIGHTING PROCEDURES

Suitable Extinguishing Media: Foam, water, dry chemical, or carbon dioxide

Hazardous Combustion Products: Carbon dioxide and carbon monoxide, oxides of nitrogen,

sulfur dioxide, partially burned carbon

Recommended Fire Fighting

Procedures:

Treat as a Class "B" fire. Limit fire fighting to those trained to

do so. Minimize breathing gases, vapor, fumes, or decomposition products. Use supplied air breathing equipment for enclosed or confined spaces or as otherwise

needed.

Unusual Fire and Explosion

Hazards:

None Known.

Firestone Building Products Company, LLC Material Safety Data Sheet

April 29, 2011 Page: 2

SECTION 6: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to Be Taken in Case Material is Released or Spilled:

Shovel or scoop into a sealable container for disposal.

Precautions to Be Taken in Handling and Storing:

Do not store or handle at temperatures in excess of 130°F. Store in a cool, dry area. Avoid prolonged or repeated contact with the skin. Product readily removed from the skin with waterless hand cleaners followed by washing with soap and

water.

SECTION 7: EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation: No special ventilation requirements.

Respiratory Protection: None required.

Eye Protection: Safety glasses with side shields may be necessary when

handling, cutting or applying this product.

Skin Protection: None required.

Other: None required.

Work / Hygienic Practices: Wash exposed skin prior to eating, drinking or smoking and at

the end of each shift. Wash contaminated clothing prior to

reuse.

SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: Formed or flat rubber with laminated tape (Peel & Stick Seam Tape has

no laminate); little odor.

Flash Point: Unknown Lower Explosive Limit: Not

Applicable

Method Used: Not Applicable Upper Explosive Limit: Not

Applicable

Evaporation Rate: Not Applicable Boiling Point: Not

Applicable

pH (undiluted product): Not Applicable Melting Point: Not

Applicable

Solubility in Water: None Specific Gravity: Unknown Vapor Density: Not Applicable Percent Volatile: Unknown

Vapor Pressure: Not Applicable

SECTION 9: STABILITY AND REACTIVITY

Thermal Stability: Stable

Hazardous Polymerization: Will not occur.

Conditions to Avoid: Storage at temperature in excess of 130°F.

Firestone Building Products Company, LLC Material Safety Data Sheet

April 29, 2011 Page: 3

l

Regulatory Agency:
Proper Shipping Name:
Not Applicable
Hazard Classification:
Not Applicable
Identification Number:
Not Applicable
Labels Required:
Not Applicable
Other Requirements:
Not Applicable

SECTION 11: MISCELLANEOUS INFORMATION

Additional Comments: This product is considered to be a finished article as per 29

CFR 1910.1200(C) and is therefore exempt from the requirements of the Hazard Communication standard.

Date of Previous MSDS: December 10, 2010

Changes Since Previous MSDS: Company name change; product description in section 8.

Telephone Number for Additional (317) 575-7190

Information:

DISCLAIMER

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Firestone Building Products Company, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Firestone Building Products Company assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.