



Edge Caulk (Black)

Description:

GenTite Edge Caulk (Black) is a one-part elastomeric sealant that is used primarily with the Cover Tape. It offers excellent adhesion to Rubber Roofing (Black) and other surfaces, as well as excellent resistance to ozone, ultra-violet, and general weathering.

Installation:

Apply GenTite Edge Caulk according to current GenTite specifications and details. Apply a continuous "high profile" bead of caulk at field seam intersections, cover tape end laps, edge metal joints. GenTite Edge Caulk may be used at other details using Cover Tape including curb/skylights, pitch pans, scuppers, perimeter edge metal, and gutters. Refer to current GenTite Application Instructions for additional application instructions.

Product Data:

SIZE	CONTENTS	PRODUCT #
326 ml (11 oz) Tube	12 Tubes per Carton	W59GT10159

Coverage Rate: A 326 ml (11 oz.) tube seals 15 L.F.

STORAGE:

Store indoors in original unopened containers at a temperature between 60 °F and 80 °F (16 °C and 27 °C) for maximum shelf life. Do not store on roof in direct sunlight. When exposed to lower temperatures, restore to room temperature prior to use.

SHELF LIFE:

12 months; shelf life will be shortened if exposed to elevated temperatures.

PRECAUTIONARY DATA:

This product is extremely flammable. Vapors may cause flash fires. Vapors may ignite explosively under certain conditions. Keep away from fire, sparks, and sources of heat. Extinguish all flames and pilot lights. Turn off electronic motors, stoves, or heaters, or any source of ignition during use and until all vapors have been dispersed. Do not smoke.

- Review Material Safety Data Sheet prior to use.
- Open all doors and windows.
- Close containers after use.
- Use with adequate ventilation.
- Avoid prolonged breathing of vapors.



Edge Caulk (Black)

- Avoid prolonged and repeated contact with skin.
- Store at temperature of 80 °F (27 °C) or below for maximum shelf life.
- Keep out of reach of children.
- Keep away from eyes.
- Use chemically resistant gloves.

Physical Properties:

PROPERTY	TYPICAL VALUES
Base	EPDM Rubber
Color	Black
Solids	80%
Solvents	Light Aliphatic Solvent
Viscosity	30-50 seconds to extrude 20 grams through 0.104" (2.64 mm) diameter orifice at 72-74° F (22.2-23.3° C)
Weight	11.2-12.2 lbs/gal (1.34-1.46 Kg/L)
Specific Gravity	1.34-1.46
Flash Point	52° F (11° C)

LEED INFORMATION:

Recycled Content Post Consumer Post Industrial	0% 0%
V.O.C. Content	<250 g/L

GenTite™ RRS
250 West 96th Street
Indianapolis, IN 46260
800-443-4272 • www.GenTite.com