



## Peel & Stick Pipe Boot (Black)

### DESCRIPTION

GenTite Peel & Stick Pipe Boots (Black) are specifically designed to be used in conjunction with Rubber Roofing (Black) roofing applications for flashing round penetrations. Each pipe boot will fit various width penetrations and can be cut to the correct pipe diameter before installation.

### INSTALLATION

Refer to current GenTite Application Instructions for additional application instructions.

**IMPORTANT: Ensure the receiving surfaces are free of debris and no moisture is present.**

1. Thoroughly mix GenTite Primer. **DO NOT THIN!** A minimum of 2 minutes of vigorous hand mixing with a wooden paint stirrer or its equivalent is required. All sources of ignition should be eliminated; adequate ventilation should exist.
2. Clean all surfaces with a clean cotton rag, removing excess contamination prior to application of the primer.
3. With a scrub pad and handle, apply GenTite Primer to the bonding area, using long and continuous back and forth strokes with heavy to moderate pressure until no streaks or puddling occurs.
4. Allow GenTite Primer to dry until slightly tacky to a dry finger touch.
5. Apply GenTite Water Stop to penetration at necessary height.
6. Cut the GenTite Peel & Stick Pipe Boot to the desired diameter and slide down the pipe until the boot is approximately 2" (50.8 mm) above the deck sheet.
7. Peel off the release paper from the underside of the pipe boot and finish sliding the boot into place.
8. Using a Teflon coated or hard rubber roller, press firmly on the pipe boot flange to ensure uniform contact.

**DO NOT TRY TO REPOSITION THE BOOT ONCE IT HAS BEEN PLACED ONTO THE DECK SHEET.**

9. Install the clamping ring.
10. Apply GenTite Caulk around the perimeter of boot flange and along any factory or field seam that may run under the boot.

### PRODUCT DATA

SIZE	QUANTITY	PRODUCT #
1" to 6" (25 mm to 152 mm) Diameter Boot	10 Pipe Boots and Clamps per Carton	W59GT10102

GenTite™ RRS  
250 West 96<sup>th</sup> Street  
Indianapolis, IN 46260  
800-443-4272 • [www.GenTite.com](http://www.GenTite.com)



## Peel & Stick Pipe Boot (Black)

### STORAGE

Store in original unopened container indoors at temperatures between 60°F (16°C) and 80°F (27°C). Do not store on roof in direct sunlight or at temperatures above 100°F (38°C). When exposed to lower temperatures, restore to room temperature prior to use.

### SHELF LIFE

12 months; shelf life will be shortened if exposed to elevated temperatures.

### PRECAUTIONARY DATA

Take care when moving, transporting, and handling, etc., to avoid sources of punctures and physical damage. Refer to Material Safety Data Sheet for additional information.

### PHYSICAL PROPERTIES

PROPERTY – PIPE BOOT	TYPICAL VALUES
Color	Black
Material	Molded EPDM
Sizes	Fits 1" O.D. to 6" O.D. (25 mm to 152 mm)
Clamp	Stainless Steel – Worm gear type (Clamps are included)
Pipe Flange	13" (330.2 mm) outside diameter
Thickness	0.055" – 0.075" (1.4 mm – 1.9 mm)
Tensile (ASTM D 412)	164 psi (1131 kPa)
Elongation (ASTM D 412)	480%
100% Modulus (ASTM D 412)	310 psi (2137 kPa)
Specific Gravity (ASTM D 297)	1.21
Shore A Durometer (ASTM D 2240)	60 ± 5
PROPERTY – TAPE	TYPICAL VALUES
Color	Black



## Peel & Stick Pipe Boot (Black)

Base	Butyl
Percent Solids	100%
Cured State	Cured
Thickness	.030" + .005" (.762 mm + .13 mm)

### LEED INFORMATION

Recycled Content	
Post Consumer	0%
Post Industrial	0%

GenTite™ RRS  
250 West 96<sup>th</sup> Street  
Indianapolis, IN 46260  
800-443-4272 • [www.GenTite.com](http://www.GenTite.com)