



Peel & Stick Pipe Boot (White)

DESCRIPTION

GenTite Peel & Stick Pipe Boots (White) are specifically designed to be used in conjunction with Rubber Roofing (White) and TPO roofing applications for flashing round penetrations. Each pipe boot will fit various width penetrations and can be cut to the correct pipe diameter before installation.

INSTALLATION

Refer to current GenTite Application Instructions for additional application instructions.

IMPORTANT: Ensure the receiving surfaces are free of debris and no moisture is present.

1. Thoroughly mix GenTite Primer. DO NOT THIN! A minimum of 2 minutes of vigorous hand mixing with a wooden paint stirrer or its equivalent is required. All sources of ignition should be eliminated; adequate ventilation should exist.
2. Clean all surfaces with a clean cotton rag, removing excess contamination prior to application of the primer.
3. With a scrub pad and handle, apply GenTite Primer to the bonding area, using long and continuous back and forth strokes with heavy to moderate pressure until no streaks or puddling occurs.
4. Allow GenTite Primer to dry until slightly tacky to a dry finger touch.
5. Apply GenTite Water Stop to penetration at necessary height.
6. Cut the GenTite Peel & Stick Pipe Boot to the desired diameter and slide down the pipe until the boot is approximately 2" (50.8 mm) above the deck sheet.
7. Peel off the release paper from the underside of the pipe boot and finish sliding the boot into place.
8. Using a Teflon coated or hard rubber roller, press firmly on the pipe boot flange to ensure uniform contact.

DO NOT TRY TO REPOSITION THE BOOT ONCE IT HAS BEEN PLACED ONTO THE DECK SHEET.

9. Install the clamping ring.
10. Apply GenTite Caulk around the perimeter of boot flange and along any factory or field seam that may run under the boot.

PRODUCT DATA

SIZE	QUANTITY	PRODUCT #
1" to 6" (25 to 152 mm) diameter Boot	10 Pipe Boots and Clamps per Carton	W59GT30107

GenTite™ RRS
250 West 96th Street
Indianapolis, IN 46260
800-443-4272 • www.GenTite.com



Peel & Stick Pipe Boot (White)

STORAGE

Store indoors in original unopened containers at a temperature between 60 °F and 80 °F (16 °C and 27 °C) for maximum shelf life. Do not store on roof in direct sunlight. When exposed to lower temperatures, restore to room temperature prior to use.

SHELF LIFE

12 months; shelf life will be shortened if exposed to elevated temperatures.

PRECAUTIONARY DATA

Take care when moving, transporting, and handling, etc., to avoid sources of punctures and physical damage. Refer to Material Safety Data Sheet for additional information.

PHYSICAL PROPERTIES

PROPERTY – PIPE BOOT	TYPICAL VALUES
Color	White
Material	Molded EPDM
Sizes	Fits 1" O.D. to 6" O.D. (25 mm to 152 mm)
Clamp	Stainless Steel – Worm gear type (Clamps are included)
Pipe Flange	13" (330.2 mm) outside diameter
Thickness	0.055" – 0.075" (1.4 mm – 1.9 mm)
PROPERTY – TAPE	TYPICAL VALUES
Color	White
Base	Rubber Polymer
Percent Solids	100%
Cured State	Cured
Thickness	.030" + .005" (.762 mm + .13 mm)

GenTite™ RRS
250 West 96th Street
Indianapolis, IN 46260
800-443-4272 • www.GenTite.com



Peel & Stick Pipe Boot (White)

LEED INFORMATION

Recycled Content	
Post Consumer	0%
Post Industrial	0%

PATENTS

The products described herein, or the methods of their use, may be covered by one or more of the following United States Patents: 5,084,119; 5,520,761; 5,976,292; 5,985,981.

GenTite™ RRS
250 West 96th Street
Indianapolis, IN 46260
800-443-4272 • www.GenTite.com