



Seam Cleaner LVOC

DESCRIPTION

GenTite RRS Seam Cleaner LVOC is designed to clean and prepare dirty Rubber Roofing (Black), Rubber Roofing (White) and TPO Roofing applications to be welded, or receive GenTite RRS Primers, Adhesives and Sealants. Membrane cleaned with GenTite RRS Seam Cleaner LVOC to receive Peel & Stick Seam Tape products shall be further prepared by the application of the appropriate primer.

INSTALLATION

1. Surfaces to be welded, or receive GenTite Primers, Adhesives and Sealants shall be clean, dry, and free of foreign materials and excess dusting agent. Remove loose contaminants using brooms or rags.
2. Clean/prepare dirty surfaces using clean cotton rags wetted with Seam Cleaner LVOC, in circular motions with heavy pressure over the affected areas. Membrane with caked dirt, including in-service TPO membrane, should be scrubbed using QuickScrubber™ Handle & Pad wetted with Seam Cleaner LVOC, followed by cleaning with clean dry rags to remove contaminants.
3. Allow surfaces cleaned with Single-Ply LVOC Splice Wash to dry completely (usually within 10 to 30 minutes) before welding, or applying Primers, Adhesives and Sealants per Firestone's current specifications and details.

PRODUCT DATA

SIZE	CONTENTS	PRODUCT #
1 gallon (3.8 Liter)	4 Pails per Carton	W59GT30121

Coverage Rate: 250-300 ft²/gallon (4.9 - 6.1 m²/L) on one side

STORAGE

Store in original unopened pails indoors at temperatures between 60 °F - 80 °F (16 °C - 27 °C) away from all sources of direct heat and ignition - this is a flammable liquid.

When exposed to lower temperatures, restore to room temperature prior to use.

Keep the material out of direct sunlight until ready for immediate use.

SHELF LIFE

Although there is no shelf life for Splice Wash, it's best to use within one year.

GenTite™ RRS
250 West 96th Street
Indianapolis, IN 46260
800-443-4272 • www.GenTite.com



Seam Cleaner LVOC

PRECAUTIONARY DATA

- Flammable liquid. Store and use away from all sources of direct heat and ignition.
- Cover tightly when not in use.
- Thinning is not allowed.
- Avoid breathing vapors.
- Do not use as a pre-wash for any tape products.
- Refer to Material Safety Data Sheet for further information.

PHYSICAL PROPERTIES

PROPERTY	TYPICAL VALUES
Solvents	Solvent Blend of Acetone & Mineral Spirits
Viscosity	Thin, free flowing
Weight/Gallon	7.45 ± 0.15 lb/gal (0.893 kg/L ± 0.018 kg/L)

LEED INFORMATION

Recycled Content:

Post Consumer 0%

Post Industrial 0%

V.O.C. Content Less than 250 g/L

GenTite™ RRS
250 West 96th Street
Indianapolis, IN 46260
800-443-4272 • www.GenTite.com