



Peel & Stick Pipe Boot (Black)

DESCRIPTION

GenTite Peel & Stick Pipe Boots (Black) are designed to be used in conjunction with Rubber Roofing (Black) roofing applications for flashing round penetrations. Each pipe boot will fit round penetrations 1" to 6" (25 mm to 152 mm) in diameter and can be trimmed to the exact pipe diameter before installation.

INSTALLATION

Refer to current GenTite Application Instructions for additional application instructions.

IMPORTANT: Ensure the receiving surfaces are free of debris and moisture.

1. Thoroughly mix GenTite Primer. **DO NOT THIN!** A minimum of 2 minutes of vigorous hand mixing with a wooden paint stirrer or its equivalent is required. All sources of ignition should be eliminated; adequate ventilation should exist.
2. Clean all surfaces to receive primer with a clean cotton rag, removing excess contamination prior to application of the primer.
3. With a scrub pad and handle, apply GenTite Primer to the splicing area, using long and continuous back and forth strokes with heavy to moderate pressure until no streaks or puddling occurs.
4. Allow GenTite Primer to dry until slightly tacky to a dry finger touch.
5. Cut the GenTite Peel & Stick Pipe Boot to the desired diameter and slide down the pipe until the boot is approximately 2" (51 mm) above the primed roofing membrane.
6. Remove the release paper from the underside of the pipe boot and finish installing the boot into place on primed membrane.
7. Using a Teflon coated or hard rubber roller, press firmly on the pipe boot flange to ensure uniform contact.
8. Apply GenTite Water Stop to penetration at necessary height.

DO NOT TRY TO REPOSITION THE BOOT ONCE IT HAS BEEN PLACED ONTO THE DECK SHEET.

9. Install the clamping ring at the top of the boot.
10. Apply GenTite Edge Caulk (black) around the perimeter of boot flange and along any factory or field seam that may run under the boot.

PRODUCT DATA

SIZE	QUANTITY	PRODUCT #
1" to 6" (25 mm to 152 mm) Diameter Boot	10 Pipe Boots and Clamps per Carton	W59GT10102

STORAGE

Store in original unopened container indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C). Do not store on roof in direct sunlight or at temperatures above 100 °F (38 °C). When exposed to lower temperatures, restore to room temperature prior to use.

GenTite™ RRS
 200 4th Avenue South
 Nashville, TN 37201
 800-443-4272 • www.GenTite.com



Peel & Stick Pipe Boot (Black)

SHELF LIFE

24 months; shelf life will be shortened if exposed to elevated temperatures.

PRECAUTIONARY DATA

Take care when moving, transporting, and handling, etc., to avoid sources of punctures and physical damage. Refer to Safety Data Sheet (SDS) for additional information.

TYPICAL PROPERTIES

PIPE BOOT	TYPICAL VALUES
Color	Black
Material	Molded EPDM
Sizes	Fits 1" to 6" outside diameter (25 mm to 152 mm)
Clamp	Stainless Steel – Worm gear type (Clamps are included)
Pipe Flange	13" (330.2 mm) outside diameter
Thickness	0.055" – 0.075" (1.4 mm – 1.9 mm)
Tensile (ASTM D 412)	164 psi (1131 kPa)
Elongation (ASTM D 412)	480%
100% Modulus (ASTM D 412)	310 psi (2137 kPa)
Specific Gravity (ASTM D 297)	1.21
Shore A Durometer (ASTM D 2240)	60 ± 5
TAPE	TYPICAL VALUES
Color	Black
Base	Synthetic Rubber
Percent Solids	100%
Cured State	Cured
Thickness	.030" + .005" (.762 mm + .13 mm)

LEED INFORMATION

Recycled Content	
Post-Consumer	0%
Post Industrial	0%