



DESCRIPTION

GenTite Peel & Stick Penetration Pocket (White) is a penetration pocket incorporating injection molding technology, ensuring uniform product quality and consistency. Each GenTite Penetration Pocket includes factory laminated tape adhesive flange, simplifying installation possible to GenTite Rubber Roofing (White) or TPO membranes.

INSTALLATION

Refer to current GenTite Application Instructions for additional application instructions.

1. Remove existing flashing materials, rust, dirt etc. from penetration before installing the GenTite Penetration Pocket.
2. Seal around the penetration prior to installation to prevent GenTite All Purpose Sealant from flowing into the roof system and possibly into the building.
3. Apply GenTite Primer to the inside of the Penetration Pocket, including the plastic reinforcing ring and roof membrane.
4. After the primer has dried, place the plastic ring centering it around the penetration. Ensure that there is a minimum of 1" of clearance between the sides of the penetration and ring to allow for All Purpose Sealant. If 1" of clearance cannot be achieved, then a field fabricated penetration pocket must be used.
5. Cut the Penetration Pocket along the line provided on the flange and up the sidewall (only necessary if the pocket cannot be fitted over the penetration). This cut will be flashed later with GenTite Flashing (not supplied with the GenTite Penetration Pockets).
6. With the release paper intact, place the pocket around the plastic ring so that the top lip of the pocket covers the plastic ring.
7. Locate the pre-cut area of the paper on the underside of the flange and remove a small area of the paper closest to the ring.
8. Using hand pressure, attach the inside of the flange to the membrane to ensure the pocket doesn't move while removing the remainder of the paper.
9. Remove the remainder of the release paper and roll the flange from the inside to the outside edge using a rubber seam roller.
10. Install GenTite All Purpose Sealant inside the Penetration Pocket, taking care to mound the sealer so water sheds away from the penetration.
11. Apply GenTite Edge Caulk to all lap edges formed by the Penetration Pocket and Flashing.

PRODUCT DATA

KIT CONTENTS	
Product Number	W59GT30108
6 Penetration Pockets	6" (152 mm) inside diameter
6 Plastic Rings	2" (50 mm) high



STORAGE

- Store in original unopened container indoors at temperatures between 60 °F and 80 °F (16 °C to 27 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (27 °C).
- When exposed to lower temperatures, restore to room temperature prior to use.

SHELF LIFE

- Two (2) Years can be expected if stored in original container.
- Shelf life will be shortened if exposed to elevated temperatures.

PRECAUTIONARY DATA

Refer to Safety Data Sheet (SDS) prior to use.

TYPICAL PROPERTIES

PENETRATION POCKET		VALUES
Color	White	
Base	Injection Molded White EPDM	
Sizes	6" (152 mm) inside diameter, 2" (50 mm) high, 0.060" (1.1 mm) thick with 3" (76 mm) pre-taped flange	
TAPE		VALUES
Color	White	
Base	Synthetic Rubber	
Solids	100%	
Cure State	Cured	
Thickness	0.025" ± 0.005" (0.635 mm ± 0.13 mm)	
PLASTIC RING		VALUES
Color	White or Black	
Base	Schedule 40 PVC	
Shape	Round pre-cut in one place; supports GenTite Penetration Pocket	
Sizes	6" (152 mm) inside diameter, 2" (50 mm) high, 0.31" (8 mm) wall thickness	

LEED INFORMATION

Recycled Content

Post Consumer	0%
Post Industrial	0%