



DESCRIPTION

GenTite Seam Cleaner is designed to clean and prepare EPDM Rubber Roofing (Black and White) and TPO Roofing applications to receive GenTite RPS Seam Cleaner to receive Peel & Stick™ tape products shall be further prepared by the application of the appropriate primer.

INSTALLATION

Refer to current GenTite Application Instructions for additional application instructions. Apply liberal amounts of Seam Cleaner to clean cotton rag.

1. Remove all visible contaminants and maintain surfaces free from all moisture, oil, and other contaminants.
2. Using a scrubbing motion, remove all contaminants at least 2" (50 mm) past the area to be spliced.
3. Change rags frequently to avoid depositing previously removed materials.
4. Allow the cleaned membrane to dry completely before continuing seaming procedures.

PRODUCT DATA

SIZE	QUANTITY	PRODUCT #
1 Gallon (3.8 Liter) Can	4 Cans per Carton	W59GT10093

COVERAGE RATE

250-300 sq/ft per gallon (4.9 – 6.1 m²/L) on one side

STORAGE

Store in original unopened containers at a temperature between 60 °F and 80 °F (16 °C and 27 °C) away from all sources of direct heat and ignition – this is a flammable liquid. When exposed to lower temperatures, restore to room temperatures prior to use. Keep the material out of direct sunlight until ready for immediate use.

SHELF LIFE

There is no shelf life for Seam Cleaners, but it is recommended to use within two years.

PRECAUTIONARY DATA

- This product is extremely flammable. Vapors may cause flash fires. Vapors may ignite explosively under certain conditions. Keep away from fire, sparks, and sources of heat. Extinguish all flames and pilot lights. Turn off electronic motors, stoves, or heaters, or any source of ignition during use and until all vapors have been dispersed. Do not smoke.
- Close containers after use.
- Use with adequate ventilation.
- Avoid prolonged breathing of vapors.
- Avoid prolonged and repeated contact with skin.
- Keep out of reach of children.
- Keep away from eyes.
- Use chemical resistant gloves when handling.
- Review Safety Data Sheet prior to use.

GenTite™ RRS
250 West 96th Street
Indianapolis, IN 46260

800-443-4272 • www.GenTite.com



TYPICAL PROPERTIES

PROPERTY	TYPICAL VALUES
Composition	Naphthenic Solvents
Color	Clear
Viscosity	Free Flowing
Weight	6.25 ± .25 lb/gal (.77 ± 0.05 kg/L)
V.O.C. Content	750 g/L

LEED INFORMATION

Recycled Content	
Post Consumer	0%
Post Industrial	0%