



Peel & Stick Cover Tape (White)

DESCRIPTION

GenTite Peel & Stick Cover Tape (White) is a semi-cured white EPDM membrane laminated to cured Butyl based tape. GenTite Cover Tape is designed to provide a high strength, watertight seal when used to strip in seams or metal edges.

INSTALLATION

Refer to current GenTite Application Instructions for additional application instructions.

1. Thoroughly mix GenTite Primer. DO NOT THIN! A minimum of 2 minutes of vigorous hand mixing with a wooden paint stirrer or its equivalent is required. All sources of ignition should be eliminated; adequate ventilation should exist.
2. With a scrub pad and handle, apply GenTite Primer to the membrane and metal flange using long and continuous back and forth strokes with heavy to moderate pressure along the bonding area until no streaks or puddling occurs.
3. Allow GenTite Primer to dry until slightly tacky to a dry finger touch.
4. Peel the release paper from the tape and wrap around the roll one revolution. Center the tape over the area to be covered. Unroll the tape and remove the release paper in a continuous movement by pinning the paper to the roof with feet or knees.
5. Using a silicon coated roller, hand-roll the entire length of the tape into the primed surface assuring adhesion.
6. Apply a continuous "high profile" bead of edge caulk along both sides of Cover Tape, field seam intersections, Cover Tape end laps and edge metal joints. All caulking details will be completed per standard specifications with GenTite Edge Caulk.

PRODUCT DATA

SIZE	QUANTITY	PRODUCT #
6" x 50' (152.4 mm x 15.24 m)	2 Rolls per Carton	W59GT30092

STORAGE

Store indoors in original unopened containers at a temperature between 60 °F and 80 °F (16 °C and 27 °C) for maximum shelf life. Do not store on roof in direct sunlight. When exposed to lower temperatures, restore to room temperature prior to use.

SHELF LIFE

9 months; shelf life will be shortened if exposed to elevated temperatures.



PRECAUTIONARY DATA

To avoid sources of punctures and physical damage, take care when moving, transporting, or handling. Refer to Material Safety Data Sheet for additional information.

PHYSICAL PROPERTIES

EPDM PROPERTY	TYPICAL VALUES
Color	White
Base	EPDM
Solids	100%
Cure State	Semi-cured
Thickness	.060" (1.5 mm) ± 10%
TAPE PROPERTY	TYPICAL VALUES
Color	White
Base	Rubber Polymer
Solids	100%
Cure State	Cured
Thickness	.025" ± .007" (.635 mm ± .18 mm)

LEED INFORMATION

Recycled Content	
Post Consumer	0%
Post Industrial	0%

PATENTS

The products described herein, or the methods of their use, may be covered by one or more of the following United States Patent: 5,520,761; 5,976,292; 5,985,981; 6,426,129.