



Peel & Stick Cover Tape (Black)

DESCRIPTION

GenTite Peel & Stick Cover Tape (Black) is a semi-cured EPDM membrane laminated to cured Butyl based tape. GenTite Cover Tape is designed to provide a high strength, watertight seal when used to strip in seams or metal edges.

INSTALLATION

Refer to current GenTite Application Instructions for additional application instructions.

1. Thoroughly mix GenTite Primer. **DO NOT THIN!** A minimum of 2 minutes of vigorous hand mixing with a wooden paint stirrer or its equivalent is required. All sources of ignition should be eliminated; adequate ventilation should exist.
2. With a scrub pad and handle, apply GenTite Primer to the membrane and metal flange using long and continuous back and forth strokes with heavy to moderate pressure along the bonding area until no streaks or puddling occurs.
3. Allow GenTite Primer to dry until slightly tacky to a dry finger touch.
4. Peel the release paper from the tape and wrap around the roll one revolution. Center the tape over the area to be covered. Unroll the tape and remove the release paper in a continuous movement by pinning the paper to the roof with feet or knees.
5. Using a silicon coated roller, hand-roll the entire length of the tape into the primed surface assuring adhesion.
6. Apply a continuous "high profile" bead of edge caulk along both sides of Cover Tape, field seam intersections, Cover Tape end laps and edge metal joints. All caulking details will be completed per standard specifications with GenTite Edge Caulk.

PRODUCT DATA

SIZE	CONTENTS	PRODUCT #
6" x 50' (152 mm x 15.2 m) Roll	2 Roll per Carton	W59GT10168

STORAGE

Store in original unopened container indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C). Do not store on roof in direct sunlight or at temperatures above 100 °F (38 °C). When exposed to lower temperatures, restore to room temperature prior to use.

SHELF LIFE

12 months; shelf life will be shortened if exposed to elevated temperatures.

GenTite™ RRS
 200 4th Avenue South
 Nashville, TN 37201
 800-443-4272 • www.GenTite.com



Peel & Stick Cover Tape (Black)

PRECAUTIONARY DATA

- Refer to Safety Data Sheet (SDS) prior to use.
- To avoid sources of punctures and physical damage, take care when moving, transporting, or handling.

TYPICAL PROPERTIES

EPDM	TYPICAL VALUES
Color	Black
Base	EPDM
Solids	100%
Cure State	Semi-cured
Thickness	.040" min. - .007", /+ .017" (1.016 mm - .178 mm, /+ .432 mm)
Width	6" + 0", - 1/8" (152.4 mm + 0 mm, - 8 mm)
TAPE	TYPICAL VALUES
Color	Black
Base	Butyl
Solids	100%
Cure State	Cured
Thickness	.035" ± .005" (.89 mm ± .127 mm)
Width	6 1/8" + 3/8", - 0" (156 mm + 24 mm, - 0 mm)

LEED INFORMATION

Recycled Content	
Post-Consumer	0%
Post Industrial	0%