



All Purpose Sealant

DESCRIPTION

GenTite All Purpose Sealant is a one-part polyurethane moisture-curing sealant. It can be used as an exterior sealant on termination bars or used to caulk sheet metal, masonry, concrete block or as a fastener sealer over fastener heads. This product is NOT intended to be used as an edge caulk.

INSTALLATION

Refer to current GenTite Application Instructions for additional application instructions.

1. Apply All Purpose Sealant only on clean, dry surfaces. Surfaces onto which the sealant is used shall be free from loose concrete, stone, mortar, foreign materials, and other contaminants.
2. Use All Purpose Sealant to assure watertight seal between the Termination Bar and parapet wall.
3. Apply sealant into the reservoir channel creating a 100% seal between the termination bar and the wall.
4. All Purpose Sealant can be applied directly from the cartridge using a standard hand gun.
5. Apply All Purpose Sealant to substrates above 40 °F (4 °C).

CLEAN UP

Use mineral spirits or GenTite Seam Cleaner while material is fresh. After All Purpose Sealant cures, it can be removed by abrasion or mechanical means.

PRODUCT DATA

SIZE	CONTENTS	PRODUCT #
300 ml (10 oz) Tubes	12 Tubes per Carton	W59GT10172

COVERAGE RATE

A 300 ml (10 oz) cartridge seals 24 linear feet in a ¼" x ¼" (6.4 mm x 6.4 mm) joint.

STORAGE

Store indoors in original unopened containers at a temperature between 60 °F and 80 °F (16 °C and 27 °C) for maximum shelf life. Do not store on roof in direct sunlight. When exposed to lower temperatures, restore to room temperature prior to use.

SHELF LIFE

24 months; shelf life will be shortened if exposed to elevated temperatures.

GenTite™ RRS
200 4th Avenue South
Nashville, TN 37201

800-443-4272 • www.GenTite.com



All Purpose Sealant

PRECAUTIONARY DATA

This product is extremely flammable. Vapors may cause flash fires. Vapors may ignite explosively under certain conditions. Keep away from fire, sparks, and sources of heat. Extinguish all flames and pilot lights. Turn off electronic motors, stoves, or heaters, or any source of ignition during use and until all vapors have been dispersed. Do not smoke.

- Refer to Safety Data Sheet (SDS) prior to use.
- Open all doors and windows.
- Close containers after use.
- Use with adequate ventilation.
- Avoid prolonged breathing of vapors.
- Avoid prolonged and repeated contact with skin.
- Keep out of reach of children.
- Keep away from eyes.
- Use chemically resistant gloves.

TYPICAL PROPERTIES

PRODUCT	TYPICAL VALUES
Base	Polyurethane
Color	Grey
Solids	92.5 % +/- 2
Tooling Time	Less than 20 minutes
UV & Ozone Resistance	Excellent
Specific Gravity	1.186 ± 0.024
Cure Systems	Moisture Activated

LEED INFORMATION

Recycled Content	
Post-Consumer	0%
Post Industrial	0%

GenTite™ RRS
 200 4th Avenue South
 Nashville, TN 37201

800-443-4272 • www.GenTite.com