



Seam Cleaner

DESCRIPTION

GenTite Seam Cleaner is to be used on all Rubber Roofing (Black), Rubber Roofing (White), and TPO Roofing applications prior to application of Seam Adhesive or Peel & Stick Seam Tape.

INSTALLATION

Refer to current GenTite Application Instructions for additional application instructions.

1. Apply liberal amounts of Seam Cleaner to clean rag.
2. Using a scrubbing motion, remove all contaminants at least 2" (50 mm) each way from the area to be spliced.
3. Remove all visible contaminants and maintain surfaces free from all moisture, oil, and other contaminants.
4. Change rags frequently to avoid depositing previously removed materials.
5. Allow the cleaned membrane to dry completely before continuing seaming procedures.

PRODUCT DATA

SIZE	QUANTITY	PRODUCT #
6" x 1 Gallon (3.8 Liter) Can	4 Cans per Carton	W59GT10093

STORAGE

Store indoors in original unopened containers at a temperature between 60 °F and 80 °F (16 °C and 27 °C) for maximum shelf life. Do not store on roof in direct sunlight. When exposed to lower temperatures, restore to room temperature prior to use.

SHELF LIFE

24 months; shelf life will be shortened if exposed to elevated temperatures.

GenTite™ RRS
200 4th Avenue South
Nashville, TN 37201

800-443-4272 • www.GenTite.com



PRECAUTIONARY DATA

- Refer to Safety Data Sheet (SDS) prior to use.
- This product is extremely flammable. Vapors may cause flash fires. Vapors may ignite explosively under certain conditions. Keep away from fire, sparks, and sources of heat. Extinguish all flames and pilot lights. Turn off electronic motors, stoves, or heaters, or any source of ignition during use and until all vapors have been dispersed. Do not smoke.
- Open all doors and windows.
- Close containers after use.
- Use with adequate ventilation.
- Avoid prolonged breathing of vapors.
- Avoid prolonged and repeated contact with skin.
- Store at temperature of 80 °F (27 °C) or below for maximum shelf life.
- Keep out of reach of children.
- Keep away from eyes.
- Use chemically resistant gloves.

TYPICAL PROPERTIES

PROPERTY	TYPICAL VALUES
Composition	Naphthenic Solvents
Color	Clear
Solids	0.0%
Viscosity	Free Flowing
Weight	6.25 ± .25 lb/gal (.77 ± 0.05 kg/L)
Flash Point	45 °F (-12 °C) TCC
Tolerance Limit	Naphtha 500 parts per million in air

LEED INFORMATION

Recycled Content	
Post Consumer	0%
Post Industrial	0%
V.O.C. Content	750 g/L