



Seam Cleaner LVOC

DESCRIPTION

GenTite RRS Seam Cleaner LVOC is designed to clean and prepare EPDM Rubber Roofing (Black & White) and TPO Roofing applications to receive GenTite RRS Primers, Adhesives and Sealants. Membrane cleaned with GenTite RRS Seam Cleaner LVOC to receive Peel & Stick™ Seam Tape products shall be further prepared by the application of the appropriate primer.

INSTALLATION

Refer to current GenTite Application Instructions for additional application instructions.

1. Apply Liberal amounts of Seam Cleaner LVOC to clean cotton rag.
2. Remove all visible contaminants and maintain surfaces free from all moisture, oil, and other contaminants.
3. Using a scrubbing motion, remove all contaminants at least 2" (50 mm.) past the area to be spliced.
4. Change rags frequently to avoid depositing previously removed material.
5. Allow the cleaned membrane to dry completely before continuing seaming procedure.

PRODUCT DATA

SIZE	CONTENTS	PRODUCT #
1 gallon (3.8 Liter)	4 Pails per Carton	W59GT30121

Coverage Rate: 250-300 ft²/gallon (4.9 - 6.1 m²/L) on one side

STORAGE

Store in original unopened pails indoors at temperatures between 60 °F - 80 °F (16 °C - 27 °C) away from all sources of direct heat and ignition - this is a flammable liquid.

When exposed to lower temperatures, restore to room temperature prior to use.

Keep the material out of direct sunlight until ready for immediate use.

SHELF LIFE

Although there is no shelf life for Seam Cleaner LVOC, it is best to use within two years.

PRECAUTIONARY DATA

Flammable liquid. Store and use away from all sources of direct heat and ignition.

Cover tightly when not in use.

Thinning is not allowed.

Avoid breathing vapors.

Do not use as a primer for any for any tape products.

Refer to Safety Data Sheet for further information.

Use chemical resistant gloves when handling.



TYPICAL PROPERTIES

PROPERTY	TYPICAL VALUES
Composition	Solvent Blend of Acetone & Mineral Spirits
Color	Clear
Viscosity	Thin, free flowing
Weight/Gallon	7.45 ± 0.15 lb/gal (0.893 kg/L ± 0.018 kg/L)
V.O.C. Content	Less than 250 g/L

LEED INFORMATION

Recycled Content:

Post Consumer 0%
Post Industrial 0%