



EDGE Caulk (Black)

DESCRIPTION

GenTite Edge Caulk (Black) is a one-part elastomeric sealant that is used primarily with the Cover Tape. It offers excellent adhesion to Rubber Roofing (Black) and other surfaces, as well as excellent resistance to ozone, ultra-violet, and general weathering.

INSTALLATION

Apply GenTite Edge Caulk according to current GenTite specifications and details. Apply a continuous "high profile" bead of caulk at field seam intersections, cover tape end laps, edge metal joints. GenTite Edge Caulk may be used at other details using Cover Tape including curb/skylights, pitch pans, scuppers, perimeter edge metal, and gutters. Refer to current GenTite Application Instructions for additional application instructions.

PRODUCT DATA

SIZE	CONTENTS	PRODUCT #
326 ml (11 oz) Tube	12 Tubes per Carton	W59GT10159

COVERAGE RATE

A 326 ml (11 oz.) tube seals 15' (4.6 m).

STORAGE

Store indoors in original unopened containers at a temperature between 60 °F and 80 °F (16 °C and 27 °C) for maximum shelf life. Do not store on roof in direct sunlight. When exposed to lower temperatures, restore to room temperature prior to use.

SHELF LIFE

24 months; shelf life will be shortened if exposed to elevated temperatures.



PRECAUTIONARY DATA

This product is extremely flammable. Vapors may cause flash fires. Vapors may ignite explosively under certain conditions. Keep away from fire, sparks, and sources of heat. Extinguish all flames and pilot lights. Turn off electronic motors, stoves, or heaters, or any source of ignition during use and until all vapors have been dispersed. Do not smoke.

- Refer to Safety Data Sheet (SDS) prior to use.
• Open all doors and windows.
• Close containers after use.
• Use with adequate ventilation.
• Avoid prolonged breathing of vapors.
• Avoid prolonged and repeated contact with skin.
• Store at temperature of 80 °F (27 °C) or below for maximum shelf life.
• Keep out of reach of children.
• Keep away from eyes.
• Use chemically resistant gloves.

TYPICAL PROPERTIES

Table with 2 columns: PROPERTY and TYPICAL VALUES. Rows include Base (EPDM Rubber), Color (Black), Solids (80%), Solvents (Light Aliphatic Solvent), Viscosity (30-50 seconds to extrude 20 grams through 0.104" (2.6 mm) diameter orifice at 72-74 °F (22-23 °C)), Weight (11.2 - 12.2 lb/gal (1.34 - 1.46 Kg/L)), Specific Gravity (1.34 - 1.46), and Flash Point (52 °F (11 °C)).

LEED INFORMATION

Table with 2 columns: Property and Value. Rows include Recycled Content (Post-Consumer 0%, Post Industrial 0%) and V.O.C. Content (<250 g/L).