



DESCRIPTION

GenTite Water Stop is a one-component self-wetting, butyl blend mastic designed to be used as a sealing agent between the GenTite membrane and non-porous substrate in termination details. Water Stop is an extremely tacky material and will remain tacky when used in compression type terminations.

INSTALLATION

Refer to current GenTite Application Instructions for additional application instructions.

1. Apply GenTite Water Stop only on clean, dry surfaces in accordance with the appropriate GenTite specifications or details.
2. Surfaces to receive Water Stop shall be free from loose concrete, stone, mortar, foreign materials, and other contaminants.
3. Apply a minimum 9 mm (3/8") bead to substrate surface. Position the mating surface of the flashing or membrane into contact with the mastic. Roll or press the flashing or membrane firmly against the seal and substrate avoiding wrinkles to assure a complete seal.
4. Apply appropriate termination material and secure to provide constant compression for the Water Stop.

PRODUCT DATA

SIZE	QUANTITY	PRODUCT #
11 fl. oz (326 mL) Tube	12 Tubes per Carton	W59GT10160

Coverage Rate: 20' bead 3/8" (9 mm) per 10 oz (6 m per 296 cm³) per tube

STORAGE

Store indoors in original unopened containers at a temperature between 60°F and 80°F (16°C and 27°C) for maximum shelf life. Do not store on roof in direct sunlight. When exposed to lower temperatures, restore to room temperature prior to use.

SHELF LIFE

24 months; shelf life will be shortened if exposed to elevated temperatures.



PRECAUTIONARY DATA

This product is extremely flammable. Vapors may cause flash fires. Vapors may ignite explosively under certain conditions. Keep away from fire, sparks, and sources of heat. Extinguish all flames and pilot lights. Turn off electronic motors, stoves, or heaters, or any source of ignition during use and until all vapors have been dispersed. Do not smoke.

Close containers after use.

Use with adequate ventilation.

Avoid prolonged breathing of vapors.

Avoid prolonged and repeated contact with skin.

Store at temperature of 80 °F (27 °C) or below for maximum shelf life.

Keep out of reach of children.

Keep away from eyes.

Use chemically resistant gloves when handling.

Review Safety Data Sheet prior to use.

TYPICAL PROPERTIES

PROPERTY	TYPICAL VALUES
Color	Grey
Solids Percent	82% minimum
Viscosity ASTM D 1824 #7 @ 2 rpm	2,000,000 cps ± 300,000 cps
Weight	10-10.83 lb/gal (1.2 – 1.3 kg/L)
Bond Strength	Will not release from substrate
Specific Gravity	1.20 – 1.30
V.O.C. Content	115 g/L

LEED INFORMATION

Recycled Content	
Post Consumer	0%
Post Industrial	0%