Safety Data Sheet GenTite RRS

Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product identifier

Product Name • Edge Caulk White

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s) • Sealant

1.3 Details of the supplier of the safety data sheet

Manufacturer • 26 Century Boulevard, Suite 205,

Nashville, Tennessee 37214

• Telephone (General) • 800-428-4442

1.4 Emergency telephone number

Manufacturer • (800) 424-9300 - CHEMTREC

• (703) 527-3887 - CHEMTREC - International

Section 2: Hazards Identification

EU/EEC

According to: Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]

2.1 Classification of the substance or mixture

• Flammable Solids 1 - H228

Skin Irritation 2 - H315 Eye Irritation 2 - H319

Specific Target Organ Toxicity Repeated Exposure 2 - H373

2.2 Label Elements

CLP

DANGER







Hazard statements • H228 - Flammable solid

H315 - Causes skin irritation

H319 - Causes serious eve irritation

H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention • P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.

P240 - Ground and/or bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting/equipment.

P264 - Wash thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Response • P370+P378 - In case of fire: Use appropriate media for extinction.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P321 - Specific treatment, see supplemental first aid information. P362 - Take off contaminated clothing and wash before reuse. P332+P313 - If skin irritation occurs: Get medical advice/attention.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention.

P314 - Get medical advice/attention if you feel unwell.

Storage/Disposal • P501 - Dispose of content and/or container in accordance with local, regional,

national, and/or international regulations.

2.3 Other Hazards

CLP
 According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

2.1 Classification of the substance or mixture

OSHA HCS 2012 • Flammable Solids 1

Skin Irritation 2 Eye Irritation 2A Reproductive Toxicity 2

Specific Target Organ Toxicity Repeated Exposure 2

2.2 Label elements

OSHA HCS 2012

DANGER







Hazard statements · Flammable solid

Causes skin irritation

Causes serious eye irritation

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention • Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.

Ground and/or bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment.

Do not breathe mist/vapours/spray. Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

Response • In case of fire: Use appropriate media for extinction.

If on skin: Wash with plenty of water.

Specific treatment, see supplemental first aid information. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Preparation Date: 04/December/2015 Revision Date: March 25, 2024 **Storage/Disposal** • Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

2.3 Other hazards

OSHA HCS 2012

• Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to: WHMIS

2.1 Classification of the substance or mixture

WHMIS

 Flammable Solids - B4 Other Toxic Effects - D2B

2.2 Label elements

WHMIS





Flammable Solids - B4
 Other Toxic Effects - D2B

2.3 Other hazards

WHMIS

 In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

Section 3 - Composition/Information on Ingredients

3.1 Substances

• Material does not meet the criteria of a substance.

3.2 Mixtures

	Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments	
Light aliphatic solvent naphtha	CAS:64742-89-8 EC Number:265-192-2 EU Index:649-267-00-0	5% TO 20%	NDA	EU CLP: Annex VI, Table 3.1: Carc. 1B, H350; Muta. 1B, H340; Asp. Tox. 1, H304 OSHA HCS 2012: Not Classified	Carcinogen and mutagen classifications listed on EU Annex VI don't apply as this component contains less than 0.1% benzene	
Solvent naphtha (petroleum), medium aliph.	CAS:64742-88-7 FC Number:265-191-7 EU Index:649-405-00-X	2.5% TO 10%	NDA	EU CLP: Annex VI, Table 3.1: STOT RE 1 (CNS, InhI), H372; Asp. Tox. 1, H304 OSHA HCS 2012: Flam. Liq. 3; Asp. Tox. 1; STOT RE 2; Repr. 2;	NDA	

Titanium dioxide	CAS:13463-67-7 FC Number:236-675-5	<= 2.5%	NDA	EU CLP: Muta. 2, H341; Carc. 2, H351; STOT RE 2 (lungs), H373 OSHA HCS 2012: Muta. 2; Carc. 2; STOT RE 2 (Lungs)	NDA
Calcium oxide	CAS:1305-78-8 EC Number:215- 138-9	<= 1%	NDA	EU CLP: Skin Corr. 1C, H314; Eye Dam. 1, H318 OSHA HCS 2012: Skin Corr. 1C; Eye Dam. 1	NDA
Quartz	CAS:14808-60-7 FC Number:238-878-4	<= 0.5%	NDA	EU CLP: Carc. 1A, H350i; STOT RE 1, H372 (Lungs, Inhl) OSHA HCS 2012: Carc. 1A; STOT RE 1 (Lungs, Inhl)	NDA

It is highly unlikely the powders and pigments compounded within this product would pose a hazardous risk from inhalation as they are no longer a respirable particulate. Exposure to these ingredients as used in sealants, putties, bedding compounds and other non-sprayable products is highly unlikely.

See Section 16 for full text of H-statements.

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

 Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. Get medical attention if symptoms occur.

Skin

 In case of contact with substance, immediately flush skin with running water for at least 20 minutes. If skin irritation occurs: Get medical advice/attention.

Eye

• In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.

Ingestion

Get medical attention immediately.

4.2 Most important symptoms and effects, both acute and delayed

· Refer to Section 11 - Toxicological Information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

All treatments should be based on observed signs and symptoms of distress in the
patient. Consideration should be given to the possibility that overexposure to materials
other than this product may have occurred.

Section 5 - Firefighting Measures

5.1 Extinguishing media

Suitable Extinguishing Media • CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Unsuitable Extinguishing Media

No data available

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

Flammable/combustible material.

May be ignited by friction, heat, sparks or flames. Some may burn rapidly with flare burning effect.

Powders, dusts, shavings, borings, turnings or cuttings may explode or burn with explosive violence.

May re-ignite after fire is extinguished.

Hazardous Combustion Products

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Move containers from fire area if you can do it without risk.
 Wear positive pressure self-contained breathing apparatus (SCBA).
 Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

• Use only with adequate ventilation. Do not walk through spilled material. Wear appropriate personal protective equipment, avoid direct contact. Avoid contact with skin, eyes, and clothing.

Emergency Procedures

• ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). As an immediate precautionary measure, isolate spill or leak area in all directions for at least 50 meters (150 feet) for liquids and at least 25 meters (75 feet) for solids. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions. Keep unauthorized personnel away. Stay upwind. Keep out of low areas.

6.2 Environmental precautions

Prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

 SMALL DRY SPILLS: With clean shovel place material into clean, dry container and cover loosely; move containers from spill area.
 LARGE SPILLS: Wet down with water and dike for later disposal.

6.4 Reference to other sections

 Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

Do not use in areas without adequate ventilation. Keep containers closed. Keep away from heat, sparks, and flame – No Smoking. All equipment used when handling the product must be grounded. Take precautionary measures against static charges. Do not use sparking tools. Wear appropriate personal protective equipment. Avoid contact with eyes, skin and clothing. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Store in a well-ventilated place. Keep container tightly closed.

7.3 Specific end use(s)

· Refer to Section 1.2 - Relevant identified uses.

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

				Exposure Limits	/Guidelines				
	Result	ACGI	Н	Belgium	Canada Alberta	Canada Colui		Canada Manitoba	
Quartz (14808-60-7)	TWAs	0.025 mg/m3 (respirable fr		0.1 mg/m3 TWA (alveolar dust)	0.025 mg/m3 TWA (respirable particulate)	0.025 mg/m (respirable)		0.025 mg/m3 TWA (respirable fraction)	
Calcium oxide (1305-78-8)	TWAs	2 mg/m3 TW/	Ą	2 mg/m3 TWA	2 mg/m3 TWA	2 mg/m3 TV	VA	2 mg/m3 TWA	
Titanium dioxide (13463-67-7)	TWAs	10 mg/m3 TV	VA	10 mg/m3 TWA	10 mg/m3 TWA	10 mg/m3 T dust); 3 mg/ (respirable	/m3 TWA	10 mg/m3 TWA	
			E	xposure Limits/Gu	idelines (Con't.)				
	Result	Canada Brunsv	-	Canada Northwest Territories	Canada Nova Scotia	Canada I	Nunavut	Canada Ontario	
Quartz (14808-60-7)	TWAs	0.1 mg/m3 TV (respirable fr		0.1 mg/m3 TWA (respirable mass); 0.3 mg/m3 TWA (total mass)	0.025 mg/m3 TWA (respirable fraction)	0.1 mg/m3 (respirable 0.3 mg/m3 mass)	mass);	0.10 mg/m3 TWA (designated substances regulation, respirable listed under Silica, crystalline)	
Calcium oxide	TWAs	2 mg/m3 TW/	٩	2 mg/m3 TWA	2 mg/m3 TWA	2 mg/m3 TV	VA	2 mg/m3 TWA	
(1305-78-8)	STELs	Not establish	ed	4 mg/m3 STEL	Not established	4 mg/m3 ST	EL	Not established	
Titanium dioxide (13463-67-7)	TWAs	10 mg/m3 TWA		5 mg/m3 TWA (respirable mass); 10 mg/m3 TWA (total mass)	10 mg/m3 TWA	5 mg/m3 TWA (respirable mass); 10 mg/m3 TWA (total mass)		10 mg/m3 TWA	
			E	xposure Limits/Gu	idelines (Con't.)				
	Result	Canada Q	uebec	Canada Saskatchewan	Canada Yukon	Denr	mark	Germany DFG	
Quartz (14808-60-7)	TWAs	0.1 mg/m3 T\ (respirable d		0.05 mg/m3 TWA (respirable fraction, listed under Silica - crystalline)	300 particle/mL TWA (listed under Silica)	0.3 mg/m3 (total); 0.1 r TWA (resp	mg/m3	Not established	
	TWAs	2 mg/m3 TW/	AEV	2 mg/m3 TWA	2 mg/m3 TWA	2 mg/m3 T\	NA	Not established	
	STELs	Not establish	ed	Not established	4 mg/m3 STEL	Not establis	shed	Not established	
Calcium oxide (1305-78-8)	Ceilings	Not established		Not established	Not established	Not established		2 mg/m3 Peak (inhalable fraction)	
	MAKs	Not established		Not established	Not established	Not established		1 mg/m3 TWA MAK (inhalable fraction)	
Titanium dioxide (13463-67-7)	TWAs	10 mg/m3 TV (containing n Asbestos an Crystalline sil dust)	o d <1%	10 mg/m3 TWA	30 mppcf TWA (as Ti); 10 mg/m3 TWA (as Ti)	6 mg/m3 T\	WA (as Ti)	Not established	
STELs		Not established		Not established	20 mg/m3 STEL (as Ti) Not establish		shed	Not established	
			E	xposure Limits/Gu	idelines (Con't.)				
		Result	1	Sermany TRGS	NIOSH			OSHA	
Quartz (14808-60-7)		TWAs	Not estat	blished	0.05 mg/m3 TWA (respirable		Not establ	shed	

Calcium oxide (1305-78-8)	TWAs	can be excluded when AGW and BGW values are observed. Substance causing local effects, inhalable fraction, exposure factor 2)	2 mg/m3 TWA	5 mg/m3 TWA
Titanium dioxide (13463-67-7)	TWAs	Not established	Not established	15 mg/m3 TWA (total dust)

Exposure Control Notations

Germany DFG

- •Titanium dioxide (13463-67-7): Carcinogens: (Category 3A (could be carcinogenic for man, inhalable fraction with the exception of ultra small particles))
- •Quartz (14808-60-7): Carcinogens: (Category 1 (causes cancer in man, alveola fraction))

8.2 Exposure controls

Engineering Measures/Controls

 This material is designed to be used outdoors, in roofing applications. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof electrical/ventilating/lighting/equipment.

Personal Protective Equipment

Respiratory

In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH or European Standard EN 149 certified respirator if exposure limits are exceeded or symptoms are experienced.

Eye/Face

· Wear safety goggles.

Skin/Body

Wear protective gloves and clothing.

Environmental Exposure Controls

In case of spills, keep product clear of sewers, waterways or land areas. Dispose of waste product in accordance with national and local laws and regulations.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

= Short Term Exposure Limits are based on 15-minute

= Maximale Arbeitsplatz Konzentration is the maximum permissible

= Time-Weighted Averages are based on 8h/day, 40h/week

concentration

exposures TWAEV = Time-Weighted Average Exposure Value

NIOSH = National Institute of Occupational Safety and Health OSHA = Occupational Safety and Health Administration

Section 9 - Physical and Chemical Properties

9.1 Information on Physical and Chemical Properties

Material Description						
Physical Form	Solid	Appearance/Description	White pasty solid with petroleum-like odor.			
Color	White	Odor	Petroleum-like			
Odor Threshold	Data lacking					
General Properties		-	-			
Boiling Point	131 °C(267.8 °F)	Melting Point/Freezing Point	Data lacking			
Decomposition Temperature	Data lacking	рН	Data lacking			
Specific Gravity/Relative Density	Data lacking	Density	Data lacking			
Bulk Density	1.42 g/cm ³	Water Solubility	Insoluble			
Viscosity	> 20.5 Centistoke (cSt, cS) or mm2/sec	Explosive Properties	Data lacking			

Preparation Date: 04/December/2015 Revision Date: March 25, 2024

Oxidizing Properties:	Data lacking						
Volatility	•	-					
Vapor Pressure	Data lacking	Vapor Density	3.8 Air=1				
Evaporation Rate	Data lacking	VOC (Vol.)	< 250 g/L				
Flammability	•	-					
Flash Point	10 °C(50 °F)	UEL	Data lacking				
LEL	Data lacking	Autoignition	Data lacking				
Flammability (solid, gas)	Data lacking						
Environmental En							
Octanol/Water Partition coefficient	Data lacking						

9.2 Other Information

No additional physical and chemical parameters noted.

Section 10: Stability and Reactivity

10.1 Reactivity

• No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

· Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

· Hazardous polymerization will not occur.

10.4 Conditions to avoid

• Avoid flames, sparks, or other sources of ignition. Incompatible materials.

10.5 Incompatible materials

· Strong oxidizing agents.

10.6 Hazardous decomposition products

· None known.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

	Components				
Titanium dioxide (<= 2.5%)		Irritation: Skin-Human • 300 µg 3 Day(s)-Intermittent • Mild irritation; Multi-dose Toxicity: Inhalation-Rat TCLo • 10 mg/m³ 6 Hour(s) 13 Week(s)-Intermittent; Lungs, Thorax, or Respiration:Fibrosis (interstitial); Lungs, Thorax, or Respiration:Other changes; Biochemical:Metabolism (intermediary):Effect on inflammation or mediation of inflammation; Inhalation-Rat TCLo • 250 mg/m³ 6 Hour(s) 4 Week(s)-Intermittent; Lungs, Thorax, or Respiration:Chronic pulmonary edema; Lungs, Thorax, or Respiration:Other changes; Mutagen: Cytogenetic analysis • Ingestion/Oral-Mouse • 280 mg/kg 7 Day(s)-Intermittent; Micronucleus test • Ingestion/Oral-Mouse • 280 mg/kg 7 Day(s)-Intermittent; DNA damage • Ingestion/Oral-Mouse • 280 mg/kg 7 Day(s)-Intermittent; Tumorigen / Carcinogen: Inhalation-Rat • 10 mg/m³ 18 Hour(s) 2 Year(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors; Inhalation-Rat TCLo • 250 mg/m³ 6 Hour(s) 2 Year(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration:Tumors			
		Multi-dose Toxicity: Inhalation-Mouse TCLo • 2200 mg/m³ 6 Hour(s) 16 Day(s)-Intermittent; Liver: Changes in liver			

Solvent n (petroleur medium a (2.5% TO	n), liph.	64742 -88-7	weight; Reproductive Effects:Paternal Effects:Spermatogenesis; Inhalation-Rat TCLo • 550 mg/m³ 6 Hour(s) 16 Day (s)-Intermittent; Kidney, Ureter, and Bladder:Other changes in urine composition; Kidney, Ureter, and Bladder:Changes in kidney weight; Reproductive Effects:Paternal Effects:Spermatogenesis; Inhalation-Rat TCLo • 550 mg/m³ 91 Day(s)-Intermittent; Kidney, Ureter, and Bladder:Changes in tubules (including acute renal failure, acute tubular necrosis); Kidney, Ureter, and Bladder:Other changes; Inhalation-Rat TCLo • 550 mg/m³ 6 Hour(s) 16 Day(s)-Intermittent; Endocrine:Thyroid tumors
Quartz (< 0.5%)		14808 -60-7	Acute Toxicity: Inhalation-Human TCLo • 16 mppcf 8 Hour(s) 17.9 Year(s)-Intermittent; Lungs, Thorax, or Respiration:Fibrosis, focal (pneumoconiosis); Lungs, Thorax, or Respiration:Cough; Lungs, Thorax, or Respiration:Dyspnea; Inhalation-Rat TCLo • 200 mg/kg; Lungs, Thorax, or Respiration:Fibrosis, focal (pneumoconiosis); Lungs, Thorax, or Respiration:Other changes; Nutritional and Gross Metabolic:Changes in Chemistry or Temperature:Fe; Multi-dose Toxicity: Inhalation-Hamster TCLo • 3 mg/m³ 6 Hour(s) 78 Week(s)-Intermittent; Lungs, Thorax, or Respiration:Fibrosis (interstitial); Lungs, Thorax, or Respiration:Changes in lung weight; Inhalation-Rat TCLo • 80 mg/m³ 26 Week(s)-Intermittent; Lungs, Thorax, or Respiration:Fibrosis, focal (pneumoconiosis); Blood:Changes in spleen; Immunological Including Allergic:Decrease in cellular immune response; Inhalation-Rat TCLo • 6.2 mg/m³ 6 Hour(s) 6 Week(s)-Intermittent; Lungs, Thorax, or Respiration:Other changes; Blood:Changes in spleen; Immunological Including Allergic:Increase in cellular immune response; Mutagen: Micronucleus test • Unreported Route-Hamster • Lung (Somatic cell) • 160 µg/cm³; DNA damage • Unreported Route-Human • Other Cell Type • 120 mg/L 24 Hour(s); Micronucleus test • Unreported Route-Human • Lung (Somatic cell) • 40 µg/cm³; Tumorigen / Carcinogen: Inhalation-Rat TCLo • 50 mg/m³ 6 Hour(s) 71 Week(s)-Intermittent; Tumorigenic:Carcinogenic by RTECS criteria; Liver:Tumors

GHS Properties	Classification
Acute toxicity	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Skin corrosion/Irritation	EU/CLP • Skin Irritation 2 OSHA HCS 2012 • Skin Irritation 2
Serious eye damage/Irritation	EU/CLP • Eye Irritation 2 OSHA HCS 2012 • Eye Irritation 2A
Skin sensitization	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Respiratory sensitization	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Aspiration Hazard	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Carcinogenicity	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Germ Cell Mutagenicity	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Toxicity for Reproduction	EU/CLP • Data lacking OSHA HCS 2012 • Toxic to Reproduction 2
STOT-SE	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
STOT-RE	EU/CLP • Specific Target Organ Toxicity Repeated Exposure 2 OSHA HCS 2012 • Specific Target Organ Toxicity Repeated Exposure 2

Potential Health Effects Inhalation

• May cause respiratory irritation.

Acute (Immediate)

Chronic (Delayed)

No data available

Skin

Acute (Immediate)

· Causes skin irritation.

Chronic (Delayed)

No data available.

Eye

Acute (Immediate)

· Causes serious eye irritation.

Chronic (Delayed)

· No data available.

Ingestion

Acute (Immediate)
Chronic (Delayed)

May cause irritation.

ed) • No data available.

Carcinogenic Effects

Although this material does contain several components that are either carcinogens or
potential carcinogens the material as a whole is not classified as a carcinogen
according to regulatory guidelines. While the following components are listed by IARC
as carcinogenic, they are bound in the matrix of this product and not expected to be
released under normal use.

Carcinogenic Effects					
CAS IARC NTP					
Quartz	14808-60-7	Group 1-Carcinogenic	Known Human Carcinogen		
Titanium dioxide	13463-67-7	Group 2B-Possible Carcinogen	Evidence of Carcinogenicity		

Key to abbreviations

LD = Lethal Dose

TC = Toxic Concentration

TD = Toxic Dose

Section 12 - Ecological Information

12.1 Toxicity

· Material data lacking.

12.2 Persistence and degradability

Material data lacking.

12.3 Bioaccumulative potential

Material data lacking.

12.4 Mobility in Soil

Material data lacking.

12.5 Results of PBT and vPvB assessment

No PBT and vPvB assessment has been conducted.

12.6 Other adverse effects

· No studies have been found.

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

• Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1325	Flammable solids, organic, n.o.s. (Naphtha)	4.1	II	NDA
TDG	UN1325	FLAMMABLE SOLID, ORGANIC, N.O.S. (Naphtha)	4.1	II	NDA
IMO/IMDG	UN1325	FLAMMABLE SOLID, ORGANIC, N.O.S. (Naphtha)	4.1	II	NDA
ADN	UN1325	FLAMMABLE SOLID, ORGANIC, N.O.S. (Naphtha)	4.1	II	NDA
ADR/RID	UN1325	FLAMMABLE SOLID, ORGANIC, N.O.S. (Naphtha)	4.1	II	NDA
IATA/ICAO	UN1325	Flammable solid, organic, n.o.s. (Naphtha)	4.1	II	NDA

14.6 Special precautions for user

· None specified.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Data lacking.

14.8 Other information

DOT • This product can qualify for the limited quantity exception found under 49 CFR § 173.151 Exceptions for Class 4.

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications • Acute, Chronic, Fire

	State Right To Know							
Component	CAS	MA	NJ	PA				
Calcium oxide	1305-78-8	Yes	Yes	Yes				
Light aliphatic solvent naphtha	64742-89-8	No	No	No				
Quartz	14808-60-7	Yes	Yes	Yes				
Solvent naphtha (petroleum), medium aliph.	64742-88-7	No	Yes	No				
Titanium dioxide	13463-67-7	Yes	Yes	Yes				

Inventory						
Component	CAS	Canada DSL	Canada NDSL	EU EINECS	EU ELNICS	TSCA
Calcium oxide	1305-78-8	Yes	No	Yes	No	Yes

Light aliphatic solvent naphtha	64742-89-8	Yes	No	Yes	No	Yes
Quartz	14808-60-7	Yes	No	Yes	No	Yes
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Yes	No	Yes	No	Yes
Titanium dioxide	13463-67-7	Yes	No	Yes	No	Yes

Canada Labor

Canada - WHMIS - Classifications of Substances

Calcium oxide	1305-78-8	E
Titanium dioxide	13463-67-7	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Titanium dioxide, mixture containing on Health Canada's WHMIS Division website.)
Light aliphatic solvent naphtha	64742-89-8	B2
Solvent naphtha (petroleum), medium aliph.	64742-88-7	B3 (petroleum, C9-12)
• Quartz	14808-60-7	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)
Canada - WHMIS - Ingredient Disclosure List		
Calcium oxide	1305-78-8	1 %
Titanium dioxide	13463-67-7	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed
• Quartz	14808-60-7	1 %
Environment Canada - CEPA - Priority Substances List		
Calcium oxide	1305-78-8	Not Listed
Titanium dioxide	13463-67-7	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed
• Quartz	14808-60-7	Not Listed

Europe

	_				
-1	\mathbf{a}	٠	h	^	
и	v.	•		œ	•

Other			
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification			
Calcium oxide	1305-78-8	Not Listed	
Titanium dioxide	13463-67-7	Not Listed	
Light aliphatic solvent naphtha	64742-89-8	Carc.Cat.2; R45 Muta.Cat.2; R46 Xn; R65	
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Xn; R48/20-65	

• Quartz	14808-60-7	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits		
Calcium oxide	1305-78-8	Not Listed
Titanium dioxide	13463-67-7	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed
• Quartz	14808-60-7	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling		
Calcium oxide	1305-78-8	Not Listed
Titanium dioxide	13463-67-7	Not Listed
Light aliphatic solvent naphtha	64742-89-8	T R:45-46-65 S:53-45
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Xn R:48/20-65 S:(2)-23-24-62
• Quartz	14808-60-7	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Pr	eparations	
Calcium oxide	1305-78-8	Not Listed
Titanium dioxide	13463-67-7	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Р
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed
• Quartz	14808-60-7	Not Listed
EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases		
Calcium oxide	1305-78-8	Not Listed
Titanium dioxide	13463-67-7	Not Listed
Light aliphatic solvent naphtha	64742-89-8	S:53-45
Solvent naphtha (petroleum), medium aliph.	64742-88-7	S:(2)-23-24-62
• Quartz	14808-60-7	Not Listed

United States

als		
1305-78-8	Not Listed	
13463-67-7	Not Listed	
64742-89-8	Not Listed	
64742-88-7	Not Listed	
14808-60-7	Not Listed	
1305-78-8	Not Listed	
13463-67-7	Not Listed	
64742-89-8	Not Listed	
64742-88-7	Not Listed	
14808-60-7	Not Listed	
	1305-78-8 13463-67-7 64742-89-8 64742-88-7 14808-60-7 1305-78-8 13463-67-7 64742-89-8 64742-88-7	1305-78-8 Not Listed 13463-67-7 Not Listed 64742-89-8 Not Listed 64742-88-7 Not Listed 14808-60-7 Not Listed 1305-78-8 Not Listed 13463-67-7 Not Listed 64742-89-8 Not Listed 64742-89-8 Not Listed

S CAA (Clean Air Act) - 1990 Hazardous Air Pollutants		
Calcium oxide	1305-78-8	Not Listed
Titanium dioxide	13463-67-7	Not Listed
ight aliphatic solvent naphtha	64742-89-8	Not Listed
olvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed
Quartz	14808-60-7	Not Listed

1305-78-8	Not Listed
13463-67-7	Not Listed
64742-89-8	Not Listed
64742-88-7	Not Listed
14808-60-7	Not Listed
1305-78-8	Not Listed
13463-67-7	Not Listed
64742-89-8	Not Listed
64742-88-7	Not Listed
14808-60-7	Not Listed
100==0.0	
	Not Listed
	Not Listed
	Not Listed
64742-88-7	Not Listed
14808-60-7	Not Listed
1205 70 0	Not Listed
	Not Listed
	Not Listed
	Not Listed
14808-60-7	Not Listed
1305-78-8	Not Listed
	Not Listed
14000-00-7	Not Listed
1305-78-8	Not Listed
	Not Listed
	Not Listed
	Not Listed
011 12 00 1	. tot Liotod
14808-60-7	Not Listed
	13463-67-7 64742-89-8 64742-88-7 14808-60-7 1305-78-8 13463-67-7 64742-89-8 64742-89-8 64742-88-7 14808-60-7 1305-78-8 13463-67-7 64742-89-8 64742-88-7 14808-60-7 1305-78-8 13463-67-7 64742-89-8 64742-88-7 14808-60-7

United States - California

Environment U.S California - Proposition 65 - Carcinogens List		
Calcium oxide	1305-78-8	Not Listed carcinogen, initial date 9/2/11
Titanium dioxide	13463-67-7	(airborne, unbound particles of respirable size)
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed
• Quartz	14808-60-7	carcinogen, initial date 10/1/88 (airborne particles of respirable size)
U.S California - Proposition 65 - Developmental Toxicity		

Calcium oxide	1305-78-8	Not Listed
Titanium dioxide	13463-67-7	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed
• Quartz	14808-60-7	Not Listed
U.S California - Proposition 65 - Maximum Allowable Dose Levels (MADL)		
Calcium oxide	1305-78-8	Not Listed
Titanium dioxide	13463-67-7	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed
• Quartz	14808-60-7	Not Listed
U.S California - Proposition 65 - No Significant Risk Levels (NSRL)		
Calcium oxide	1305-78-8	Not Listed
Titanium dioxide	13463-67-7	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed
• Quartz	14808-60-7	Not Listed
U.S California - Proposition 65 - Reproductive Toxicity - Female		
Calcium oxide	1305-78-8	Not Listed
Titanium dioxide	13463-67-7	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed
• Quartz	14808-60-7	Not Listed
U.S California - Proposition 65 - Reproductive Toxicity - Male		
Calcium oxide	1305-78-8	Not Listed
Titanium dioxide	13463-67-7	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed
• Quartz	14808-60-7	Not Listed

United States - Pennsylvania

J.S Pennsylvania - RTK (Right to Know) - Environmental Hazard	I List	
Calcium oxide	1305-78-8	Not Listed
Titanium dioxide	13463-67-7	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed
• Quartz	14808-60-7	Not Listed
J.S Pennsylvania - RTK (Right to Know) - Special Hazardous Su	ıbstances	
Calcium oxide	1305-78-8	Not Listed
Titanium dioxide	13463-67-7	Not Listed
Light aliphatic solvent naphtha	64742-89-8	Not Listed
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Not Listed
	14808-60-7	Not Listed

15.2 Chemical Safety Assessment

· No Chemical Safety Assessment has been carried out.

15.3 Other Information

Revision Date: March 25, 2024

 WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 16 - Other Information

Relevant Phrases (code & full text)

- · H304 May be fatal if swallowed and enters airways
 - H314 Causes severe skin burns and eye damage.
 - H318 Causes serious eye damage H340 May cause genetic defects.
 - H341 Suspected of causing genetic defects.
 - H350 May cause cancer.
 - H350i May cause cancer by inhalation. H351 - Suspected of causing cancer.
 - H372 Causes damage to organs through prolonged or repeated exposure.
 - H373 May cause damage to organs Lungs through prolonged or repeated exposure via Inhalation
- March 25, 2024
- 04/December/2015

Preparation Date Disclaimer/Statement of Liability

Revision Date

• The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information, is accurate, complete or representative. Holcim Solutions and Products US, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons, if reasonable safety procedures are not followed. Additionally, Holcim Solutions and Products US, LLC assumes no responsibility for injury to buyer, the buyer's employees, or any third persons caused by abnormal use of this material, even if reasonable safety procedures are followed.

Key to abbreviationsNDA = No data available